

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
7 October 2004 (07.10.2004)

PCT

(10) International Publication Number
WO 2004/085846 A1

(51) International Patent Classification⁷: F03G 6/04

(21) International Application Number:
PCT/GR2003/000037

(22) International Filing Date:
8 September 2003 (08.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
20030100150 27 March 2003 (27.03.2003) GR

CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


(71) Applicant and
(72) Inventor: PAPAGEORGIOU, Christos [GR/GR]; 1b
Nymfon Str., GR-14563 Kifissia, Athens (GR).

Published:
— with international search report

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FLOATING SOLAR CHIMNEY



(57) Abstract: The floating solar chimney is composed by three parts as appear in figure 1(a). The Main Chimney (1.1). The Heavy Base (1.2). The Folding Lower Part (1.3). The main chimney (1.1) is composed by cylindrical balloon rings D1 (fig 2) full of non flammable light gas. This cylindrical balloon rings D1 are tied up between them with the help of supporting rings D2 (fig 3) so that they form a compact thermo insulated cylindrical chimney. The compact parts of the main chimney are fastened on the mobile heavy base. The successive compact parts are separated with rings D1 full from environmental air that can go in and out, so that the dynamic independence of the successive parts is ensured. The main chimney can float; self lifted and is fastened on the seat (1.4) by the mobile heavy base (1.2). In the lower part of its heavy base is fastened the folding lower part of solar chimney (type accordion, 1.3). The air can enter and come out freely from the rings of folding lower part in order that the floating solar chimney can receive any suitable decline in order to withstand the exterior winds (fig 1b).

WO 2004/085846 A1

EU 332 465 145 45